

- 1 -

PRINT HEAD APPARATUS WITH MALFUNCTION DETECTOR

Inventor(s): Robert Paasch

5

FIELD OF THE INVENTION

✓
09415618-101299
The present invention relates to print heads used in
printers and plotters and the like and, more specifically,
10 to detecting malfunctions within such print heads.

BACKGROUND OF THE INVENTION

✓
Printers and plotters are known in the art and
include those made by Hewlett-Packard, Canon and Epson,
15 amongst others. In the discussion that follows, printers
and plotters are referred to collectively with the term
"printers". Problems associated with current printers and
print head arrangements include that the print head may
run out of ink while printing, the print head nozzle may
20 become clogged and the ink expulsion mechanism may not
fire, amongst other malfunctions. Evidence of such
malfunctions are usually detected when the printed
document is pulled out of the printer and examined
visually. At this point it is too late for appropriate
25 correction. Some types of electronic sensing are known in
the art, such as techniques for detecting when an ink
expulsion mechanism has not fired. These techniques,
however, are limited in scope and do not, for example,
detect when a nozzle is clogged or unclogged.

30 A need thus exists to detect print head malfunction
in such a manner as to eliminate or minimize corruption of

2

- 2 -

a printed image. Early detection of a malfunction permits preventative steps to be taken such as print head replacement or software based compensation within the firing algorithm, etc.

5

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a print head that can detect a malfunction therein.

10 It is another object of the present invention to provide a print head that can detect such conditions as a clogged nozzle, no fire and dry fire.

It is another object of the present invention to provide a print head that incorporates a pressure sensor and circuitry therefor that detects firing of an ink
15 expulsion mechanism and determines characteristics about the firing based on the sensed signals.

It is also an object of the present invention to provide a print head with a piezoelectric type pressure
20 sensor.

These and related objects of the present invention are achieved by use of a print head apparatus with a malfunction detector as described herein.

The attainment of the foregoing and related
25 advantages and features of the invention should be more readily apparent to those skilled in the art, after review of the following more detailed description of the invention taken together with the drawings.

- 3 -

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross sectional side view of a print head in accordance with the present invention.

Fig. 2 is a side view of a piezoelectric acoustic wave transducer in accordance with the present invention.

Fig. 3 is a side view of a portion of an interdigitated pressure wave transducer in accordance with the present invention.

Fig. 4 is a plan view of an arrangement of piezoelectric acoustic pressure wave transducers and interdigitated piezoelectric pressure wave transducers in a print head in accordance with the present invention.

Fig. 5 is a graph of illustrating the pressure on an expulsion mechanism surface versus time for a clogged nozzle firing and an unclogged nozzle firing is shown.

DETAILED DESCRIPTION

Referring to Fig. 1, a cross sectional side view of a print head 10 in accordance with the present invention is shown. Print head 10 includes a substrate in or on which is provided an ink expulsion mechanism 14. Ink expulsion mechanism 14 may expel ink through thermal or mechanical excitation or through other appropriate expulsion means. In a preferred embodiment, mechanism 14 is thermally actuated and may be implemented with a resistive element as is known in the art. Ink expulsion mechanism 14 is controlled by off-die circuitry or by a combination of on-die and off-die circuitry as is known. Representative off-die coupling is indicated by signal line 15 and contact pad 16.

- 4 -

A barrier layer 20 is formed on substrate 12 and an orifice plate 30 is formed on barrier layer 20. The substrate, barrier layer and orifice plate define an ink well or conduit 24 that channels ink from a supply (not shown) into proximity with the expulsion mechanism. An orifice or nozzle 31 through which ink is expelled is formed in the orifice plate and positioned over ink expulsion mechanism 14. Suitable material for barrier layer 20 and orifice plate 30 are known in the art.

10 Assuming that ink expulsion mechanism 14 is a thermally actuated device such as a resistor, an ink drop is expelled by essentially boiling a drop of ink through nozzle 31. During formation and collapse of a boiling ink bubble, a series of acoustic pressure waves 26
15 (hereinafter referred to as "pressure waves") are produced. These waves propagate through the components of the print head, including primarily the substrate and ink well. In the substrate (and conventional thin film layers formed thereon), both longitudinal and shear waves are
20 produced. Longitudinal waves can be detected by an interdigitated piezoelectric pressure wave transducer 50 or the like which is described in more detail with reference to Figs. 3 and 4. In ink well 24, longitudinal pressure waves are produced. These waves can be detected
25 with a piezoelectric acoustic pressure wave transducer 40 which is described in more detail with reference to Fig. 2. For purposes of the present discussion, the term "interdigitated transducer" will be used for the interdigitated piezoelectric pressure wave transducer and
30 the term "acoustic transducer" will be used for the piezoelectric acoustic pressure wave transducer. While

- 5 -

Sub
a2

both an acoustic transducer and an interdigitated transducer are described as being provided on substrate 12, it should be recognized that they need not be provided together because either transducer is capable of

5 sufficiently detecting pressure waves. The provision of both provides redundancy.

Acoustic transducer 40 and interdigitated transducer 50 are preferably coupled to processing circuit 60. Processing circuit 60 preferably includes an amplifier, a

10 filter and an analog to digital converter or related signal processing circuitry. Processing circuit 60 may be configured to provide the necessary processing to determine dry-fire, no-fire and clogged-fire conditions (that is, a misfire) or the sensor output signals can be

15 delivered to off-die logic 70 for such processing. The output of processing circuit 60 is propagated over signal line 17 to contact pad 18.

Sub
a3

Referring to Fig. 2, a side view of an acoustic transducer in accordance with the present invention is

20 shown. Fig. 2 illustrates the acoustic transducer of Fig. 1 in more detail. Fig. 2 illustrates substrate 12 on which the following layers are formed: an insulation layer 21, a conductive coupling layer 41, piezoelectric material 42, a first and a second signal conductive layer 44,45, a

25 passivation layer 47 and a surface coat layer 48. In a preferred embodiment, these layers are made of the following or a like material: insulation layer 21 is silicon dioxide (SiO_2), conductive layer 41 is tantalum aluminum (TaAl), piezoelectric material 42 is aluminum

30 nitride (AlN), first and second conductive layers or traces 44,45 are aluminum (Al), passivation layer 47

10

- 6 -

includes a first layer of silicon nitride (Si_3N_4) and a second layer of silicon carbide (SiC), and coating 48 layer is tantalum (Ta). It should be recognized that the arrangement and composition of these layers may be altered in a manner consistent with device fabrication techniques without deviating from the present invention. It should also be recognized that other piezoelectric material such as zinc oxide (ZnO) or PZT may be used and that other types of suitable pressure sensors may be used.

10 ~~The first and second conductive layers 44,45 form conductors for reading a voltage generated by piezoelectric material 42 in response to an incident pressure wave. A pressure wave traveling through the ink well compress the thin film stack, resulting in a~~
15 ~~mechanical strain in the thin film layers. In the piezoelectric layer, this strain produces a measurable electric charge across the two conductors.~~

Referring to Fig. 3, a side view of a portion of an interdigitated transducer in accordance with the present invention is shown. Fig. 3 illustrates the interdigitated transducer of Fig. 1. The layout of this transducer and its arrangement with another interdigitated transducer are shown in Fig. 4. Fig. 3 illustrates substrate 12 on which are formed insulation layer 21, piezoelectric material 52, first and second conductors 54,55 (only one of which is shown), a passivation layer 57 and a coating layer 58. The substrate, insulation layer, passivation layer and coating layer are as discussed above for acoustic transducer 40. The piezoelectric material and conductive layers are preferably similar in composition to their

- 7 -

counterparts in transducer 40, however, their areal arrangement is different as shown in Fig. 4.

Sub 95/ 5 Referring to Fig. 4, a plan view of an arrangement of acoustic transducers and interdigitated transducers in a print head in accordance with the present invention is shown. Fig. 4 illustrates substrate 12, a plurality of ink expulsion mechanisms 14, barrier layer 20, ink well 24, a plurality of acoustic transducers 40 and a plurality of interdigitated transducers 50. Orifice plate 30 would be placed over the arrangement of Fig. 4 with nozzles aligned with the ink expulsion mechanisms 14. It should be recognized that the transducer arrangement disclosed in Fig. 4 is representative and provided for pedagogical purposes. The ink expulsion mechanisms ink well and the size number and arrangement of transducers may be modified from that of Fig. 4 without departing from the present invention. Furthermore, it should be recognized that although the interdigitated transducers are shown in the ink well, since they detect pressure waves in the substrate they may be placed anywhere on the substrate including under the barrier layer.

The interdigitated transducers are preferably implemented as interdigitated conductors 54-55 placed over a corresponding pattern of piezoelectric material 52. 25 These interdigitated transducers exhibit a directional detection characteristic that is advantageous to some implementations of the present invention. Fig. 4 illustrates two interdigitated pressure wave transducers 50 and 50' that are arranged orthogonally to one another. 30 This arrangement facilitates detection of pressure waves traveling in different directions. The acoustic

- 8 -

transducers 40 of Fig. 4 are essentially as described above with references to Figs. 1 and 2. Each of transducers 40 and 50 are shown with their first and second conductors 44,45 and 54,55, respectively being
5 coupled to vias 13 (under the barrier layer) that are coupled to signal processing circuit 60 of Fig. 1.

Referring to Fig. 5, a graph illustrating the pressure on the surface of resistor or expulsion mechanism 14 verses time for a clogged nozzle firing and an
10 unclogged nozzle firing is shown. As alluded to above, the cavitation of the air bubble(s) at resistor or expulsion mechanism 14 during firing causes a considerable pressure spike on the surface of the resistor. This pressure spike is normally around 20MPa (greater than 10K PSI) and occurs
15 at approximately 13.5 μ S after firing. When the nozzle associated with a particular resistor is clogged, however, the pressure spike has a different signature. Typically it is lower in magnitude by about 15-25 percent (e.g., approximately 16Mpa) and occurs earlier (e.g., 15-20%
20 earlier, usually approximately 11 μ S). The combination of decreased magnitude and quicker response time permits differentiation of an unclogged firing from a clogged firing. The absence of a pressure wave indicates a "no-fire" event.

25 While the invention has been described in connection with specific embodiments thereof, it will be understood that it is capable of further modification, and this application is intended to cover any variations, uses, or adaptations of the invention following, in general, the
30 principles of the invention and including such departures from the present disclosure as come within known or

- 9 -

customary practice in the art to which the invention
pertains and as may be applied to the essential features
hereinbefore set forth, and as fall within the scope of
the invention and the limits of the appended claims.

03415513-101233

17